



Our Company

Founded in 1893, Ishida is a privately-owned, family-run company with worldwide headquarters in Kyoto, Japan.

A world leader in the design, manufacture and installation of weighing, packaging and quality control solutions, Ishida has vast experience and knowledge of many food sectors ranging from snacks and dry food to fresh and frozen food applications.

Ishida opened its first overseas subsidiary, Ishida Europe, in 1985. Headquartered in Birmingham, United Kingdom, it serves Europe, the Middle East, and Africa (EMEA). We have wholly-owned Ishida sales and service operations in nine countries, and have committed, experienced agents and distributors in a further 30 countries.

Working with you every step of the way

Our extensive R&D investment is directed at meeting the challenges of the fast-changing food industry around the globe. We aim to support our partners fully, from the very start of their buying process, and you will find many equipment brochures, visual animations and case studies available on our website.


When you are ready to make contact, a well-resourced network of Ishida companies, distributors and agents, extending across Europe, the Middle East and Africa, can provide advice and organise demonstrations and trials.

Installation is rapid and efficient. For integrated packing lines, we use proven project management techniques and methodologies, tuned to your key objectives and specifications.

A dedicated pan-European service engineering team helps to maximise the performance, functionality and reliability of our installed base. In addition, spares facilities are strategically placed throughout the territory, offering 24-hour delivery in most cases.



helpline • spares • service • training



ISHIDA EUROPE LIMITED
Kettles Wood Drive
Woodgate Business Park
Birmingham
B32 3DB
United Kingdom
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.com

ISHIDA CZECH REPUBLIC
Tel: +420 220 960 422
info@ishidaeurope.cz

ISHIDA ROMANIA
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.ro

ISHIDA FRANCE
Tel: +33 (0)1 48 63 83 83
Fax: +33 (0)1 48 63 24 29
info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS
Tel: +7 499 272 05 36
Fax: +7 499 272 05 37
info@ishidaeurope.ru

ISHIDA GERMANY
Tel: +49 (0)791 945 160
Fax: +49 (0)791 945 1699
info@ishida.de

ISHIDA SOUTH AFRICA
Tel: +27 (0)11 976 2010
Fax: +27 (0)11 976 2012
info@ishidaeurope.com

ISHIDA MIDDLE EAST
Tel: +971 (0)4 299 1933
Fax: +971 (0)4 299 1955
ishida@ishida.ae

ISHIDA SWEDEN
Tel: +46 (0)31 871 320
info@ishidaeurope.se

ISHIDA NETHERLANDS
Tel: +31 (0)499 39 3675
Fax: +31 (0)499 39 1887
info@ishida.nl

ISHIDA SWITZERLAND
Tel: +41 (0)41 799 7999
Fax: +41 (0)41 790 3927
info@ishida.ch

Carton-Line Checkweighers

Handling mass and volume



Carton-Line

Weight Assurance of Packages and Cartons

Carton-Line checkweighers are ideal for the inspection of boxes and bags of up to 60kg for weight compliance and to detect where items are missing.

Easily handles large items, so you don't have to

Carton-Line models ensures that the inspection process flows smoothly, handling weights from 150g all the way up to 60,000g and keeping heavy lifting by your staff to the minimum.

Impressive speed and accuracy

These checkweighers keep inspection moving at belt speeds of up to 55m/min and can detect a weight discrepancy as small as 1g, thanks to the patented Ishida high-speed load cell.

Configurable to your exact needs

A free-standing display unit makes integration into the line quick and easy, while line infeed and extension conveyors can be configured to suit your specific requirements. You can choose a roller or belt feed conveyor of either waterproof or dry construction.

A rich source of data

Data capture can take place via USB download or direct printout.

Simple set-up, operation and maintenance

The simplified, intuitive interface makes Carton-Line checkweighers easy to configure and operate.

Compliance built in

All Carton-Line checkweighers comply fully with European safety and weight directives.

Checkweighers and their essential role in quality control

Checkweighers are primarily used on production lines to detect and remove items that are outside specific weight limits. (Underweight items may lead to fines and penalties, while overweight involves giving valuable product away).

However they have many other quality control benefits, such as identifying packs that have items missing, and can be combined with other detection methods (such as metal detectors and x-ray inspection systems) to exclude packs containing foreign bodies from the production output. They can also provide valuable production data to help with analysis and planning.



Specifications		Carton - Line					
		DACS-GN-S150		DACS-GN-S300		DACS-GN-S600	
Weighing Capacity		15,000g	15,000g	30,000g	15,000g	30,000g	60,000g
Upper Limit of Indication		15,000g	15,000g	30,000g	15,000g	30,000g	60,000g
Lower Limit of Indication		150g	150g	300g	150g	300g	600g
Actual Scale Interval		1g	1g	2g	1g	2g	5g
Max. Belt Speed		10 - 55 m/min	10 - 40 m/min		5 - 20 m/min		
Protection		IP30 / IP65	IP30 / IP65		IP30 / IP65		
Operating Temperature		0 - 40°C	0 - 40°C		0 - 40°C		
Weight Conveyor Size		400mm (W) x 650mm (L)	400mm (W) x 650mm (L)		400mm (W) x 650mm (L)		
			450mm (W) x 800mm (L)		450mm (W) x 800mm (L)		
			550mm (W) x 1100mm (L)		550mm (W) x 1100mm (L)		
Infeed Conveyor	Belt	400mm (W) x 650mm (L)	✓	✓	✓	✓	✓
		450mm (W) x 800mm (L)		✓	✓	✓	✓
		550mm (W) x 1100mm (L)		✓	✓	✓	✓
Roller	400mm (W) x 650mm (L)	✓	✓	✓	✓	✓	
	450mm (W) x 800mm (L)		✓	✓	✓	✓	
	550mm (W) x 1100mm (L)		✓	✓	✓	✓	
RCU Type	Standard		✓	✓	✓	✓	
Main Body Type	Remote Main Body	✓	✓	✓	✓	✓	
Reject Device	Pusher - Roller	450mm (W) x 800mm (L)	✓	✓	✓	✓	
		500mm (W) x 800mm (L)		✓	✓	✓	
		600mm (W) x 1100mm (L)		✓	✓	✓	
Reject Bin	Roller track	✓	✓	✓	✓	✓	
Standard Interface	USB (for memory stick only)	✓	✓	✓	✓	✓	
Software and Other Options	Integrated printer	✓	✓	✓	✓	✓	
	Beacon (red/green/amber)	✓	✓	✓	✓	✓	
Period	Warranty	1 year	1 year		1 year		
Language	Multiple Language Options Available	✓	✓		✓		
Power	Consumption	225W	225W		225W		
	Voltage	220 - 240v 50-60Hz	220 - 240v 50-60Hz		220 - 240v 50-60Hz		